

# Adhesion Activator

Art.: 04.1201.9999

Bottle 250 ml

Adhesion Activator is part of the Innotec Stone Chip Repair System and the Innotec Stone Chip Repair System - VW (VAS 6083A). It is a slowly evaporating cleaner and adhesion activator suitable for removing dirt, grease and silicone from the chip-damaged area.



Base:	Aliphatic hydrocarbon
Density:	748 kg/m <sup>3</sup>
Consistency:	Liquid
Viscosity:	3 mPa.s
Solvents:	Aliphatic hydrocarbon
Flash point:	38°C
Application conditions:	+10°C to +30°C
Type of surface:	The most common paint systems
Application method:	Shake the bottle before use. Apply with a clean Innotec <a href="#">Multi Wipe</a> and rub afterwards with a dry Multi Wipe. Then allow 1 minute to evaporate.
Cleaning of hands:	With Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
EAN Code:	5400563022337

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

