

Alu Finish

Art.: 02.3107.1085
Aerosol can 500 ml

Alu Finish is a quick-drying, aluminium grey spray lacquer of OEM quality. The product shows an excellent adhesion to almost all metal and various plastic surfaces. After drying, it provides an even, scratch- and wear-resistant coating. Alu Finish gives the treated surface the perfect and natural appearance of aluminium.



Base:	Acrylic resin
Density:	734 kg/m ³
Consistency:	Thin liquid (ready-to-use in aerosol)
Solvents:	Organic solvent
Flash point:	< 0°C
Temperature resistance:	-25°C to +110°C
UV resistance:	Excellent
Water resistance:	Good
Solvent resistance:	Good, in the case of brief contact
Application conditions:	+15°C to +30°C
Type of surface:	Just about all modern plastics and metal alloys
Surface preparation:	The surface must be clean, dry and free of dust and grease. Sand the surface, preferably with a sanding block. Clean metal surfaces with Innotec Multisol or Innotec Seal and Bond Remover . Provide untreated metal with a primer (Innotec Speed Primer or Innotec Zinc Coat). Clean plastic surfaces with Innotec Repaplast Cleaner Antistatic and pre-treat them with Innotec Repaplast Primer New Formula .
Application method:	Shake can well before use. Spraying distance 25-30 cm. Apply in several thin layers. Leave 10 minutes for the product to evaporate between two layers. When spraying, protect adjacent surfaces with Innotec Masking Tape or Innotec Masking Plate . After use, invert can and spray until clear to clean the nozzle.
Dust dry:	± 5 minutes (at 20°C / 65% relative humidity)
Curing time:	After ± 2 hours (at 20°C / 65% relative humidity)
Recommended layer thickness:	Apply in several thin layers
Paintability:	After ± 2 hours
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water





Shelf life: 2 years in original, unopened packaging

Storage conditions: Store cool and dry

Type of batchcode: F

EAN Code: 5400563010723

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

