

## **TECHNICAL INFO**

## Back Fill Foam 13 mm

Art.: 05.0339.0040 Roll 400 m

Back Fill Foam is a round cord of high-grade filling foam with a closed cell structure. It is indispensable when professionally sealing extremely deep building seams and seams where there is a risk of a three-point adhesion.



Base:	Polyethylene foam
Density:	± 25 kg/m³
Dimensions:	13 mm x 400 m
Application conditions:	Depending on the type of sealant used
Type of surface:	Depending on the type of sealant used
Surface preparation:	Remove any loose parts and make sure that the surface is free of dust.
Application method:	When working, follow the technical instructions for the sealant type to be used. Choose the required thickness and length of the foam. Clean the joint and treat with an adhesion primer if necessary. Press the foam into the joint using a spatula or similar tool. The joint can now be sealed.
Cleaning of materials used:	Depending on the type of sealant used
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	Unlimited in original, unopened packaging
Storage conditions:	No restriction
Type of batchcode:	F
EAN Code:	5400563025796

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.



