

TECHNICAL INFO

Black Bull Tape

Art.: 05.0345.0000 Roll 2 x 3 m

Black Bull Tape is a unique and solid, vulcanising tape activated by stretching, which fuses to form a homogenous, airtight and watertight protection after use. The product is perfectly suitable for the quick and accurate sealing of leaks.



Base:	Silicones (liner: polyethylene)
Dimensions:	25 mm x 0,5 mm x 3 m (x 2)
Elongation at break (%):	300%
Pressure resistance:	6 > 12 bars (depending on the number of windings)
Temperature resistance:	-45°C to +220°C
UV resistance:	Good
Water resistance:	Good
Saltwater resistance:	Good
Solvent resistance:	Good
Acid resistance:	Good
Dielectric strength:	16.000 V
Electrical insulating resistance:	3 x 1014 ohm – cm
Application conditions:	Silicone tape can be applied at almost any temperature. At very low temperatures the vulcanisation will take a bit longer, but this does not influence the end result at all.
Type of surface:	Almost all surfaces, e.g. electrical cabling and plastic or metal pipes. In case of emergency repairs, Black Bull Tape can be used both on soft and hard surfaces.
Surface preparation:	The surface must be clean and free of grease (if possible).
Application method:	Remove the transparent liner and apply the tape in several layers with a 50% overlap. While doing so, stretch it up to 200%. The last winding should always be applied completely over the previous one!
Shelf life:	24 months in original, unopened packaging
Storage conditions:	Store cool and dry, at a temperature between +5°C and 20°C
Type of batchcode:	F
Other details:	ATTENTION: Black Bull Tape will vulcanize really quickly! Do not use Black Bull Tape for gas connections or gas pipes!







EAN Code: 5400563025871

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.



