

## **TECHNICAL INFO**

## **SP200**

Art.: 03.0122.9999 Aerosol can 500 ml

SP200 is a high-quality, solid and transparent silicone grease for insulation and protection of electronic contacts. Thanks to its composition, the product is also highly suitable for transparent greasing and protecting plastics, metal, rubber, glass, etc.



| Base:                         | High-quality transparent lubricant based on silicone oil and quartz crystals   |
|-------------------------------|--|
| Density:                      | 945 kg/m³  |
| Consistency:                  | Pasty (ready-to-use in aerosol)  |
| Viscosity:                    | 1,5 to 2 (according to NLGI)   |
| Flash point:                  | < 0°C  |
| Pressure resistance:          | Moderate   |
| Temperature resistance:       | -40°C to +200°C  |
| Water resistance:             | Very good  |
| Acid resistance:              | Good   |
| Corrosion resistance:         | Very good  |
| Penetration ability:          | Very good  |
| Percentage of greasing agent: | 21%  |
| Application conditions:       | -15°C to +40°C   |
| Type of surface:              | All kinds of metal, most plastics, rubber, glass, etc.   |
| Surface preparation:          | The surface must be clean, dry, free of grease and non-corroded. Clean surfaces with Innotec Multisol, Innotec Ultra Clean or Innotec Power Clean.   |
| Application method:           | Shake can well before use. When applied as lubricant, spray the product directly onto the part to be greased. When used as protection for plastics and rubber, either apply the product directly (at a distance of 15–20 cm) or use a cloth or sponge. |
| Cleaning of materials used:   | With Innotec Multisol or Innotec Power Clean   |
| Cleaning of hands:            | With Innotec Safe Hand Clean Plus and water  |
| Shelf life:                   | 2 years in original, unopened packaging  |
| Storage conditions:           | Store cool and dry   |
| Type of batchcode:            | F  |
|                               |  |







Other details: Not suitable for greasing metal on metal applications under high pressure

EAN Code: 5400563015445

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.



