

Multi Spray 1000 500 ml

Art.: 03.1118.9999

500 ml

Multi Spray 1000 is a light lubricant with strong moisture repelling properties which loosens stuck parts and protects them against corrosion. The product repels moisture by establishing a barrier between the surface and the moisture, thus protecting the surface.



Base:	Mineral oil with various additives
Density:	718 kg/m ³
Consistency:	Liquid (ready-to-use in aerosol)
Viscosity:	17,5 mPa.s (at 50°C)
Flash point:	< 0°C
Pressure resistance:	Minimum
Temperature resistance:	-20°C to +120°C
Water resistance:	Good against condensation, moderate against sprayed water
Acid resistance:	Good against acid steam, moderate against acid fluid
Corrosion resistance:	No rust after 1000 hours (steel plates at a relative humidity of 95%) No rust after 50 hours salt spray vapour test, starts rusting after 100 hours
Penetration ability:	Good
Percentage of greasing agent:	25%
Tests:	Registered by NSF (class H2), register number: 153349
Application conditions:	-20°C to +40°C
Type of surface:	All kind of metals, rubbers and plastics, except perspex
Surface preparation:	The surface must be clean, dry, free of grease and non-corroded.
Application method:	Shake can well before use. If using as a lubricant, spray the product directly onto the part for lubrication. If using as a plastic and rubber protector, spray the product directly on the surface (distance 15-20 cm) or apply it with a cloth or sponge. For a beautiful shine, polish the plastic with a clean, dry Multi Wipe .
Cleaning of materials used:	With Innotec Multisol or Innotec Power Clean
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry





Type of batchcode:	F
Other details:	OEM approved
EAN Code:	5400563016886

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

