

Colour

Art.: 02.3450

Jar 30 ml

Colour is part of the Innotec Stone Chip Repair System and the Innotec Stone Chip Repair System - VW (VAS 6083A) and is a special, nitro alkyd acrylate based paint. Due to its special composition the product has excellent fill and adhesion properties, and is extremely fast-drying. The available colours allow us to repair 80% of all car paints.



Base:	Cellulose-nitrate resin, pigments and additives in solvent
Density:	980 kg/m ³
Consistency:	Liquid
Viscosity:	25 to 30 seconds (DIN Cup 4, 20°C)
Solvents:	Ketones and esters
Flash point:	< 0°C
Temperature resistance:	Up to +110°C (short-time limit +150°C)
UV resistance:	Very good
Water resistance:	Good
Solvent resistance:	Reasonable
Application conditions:	+15°C to +25°C
Type of surface:	Almost any modern car paint
Surface preparation:	The surface must be clean, dry and free of grease. Clean surface with Innotec Adhesion Activator .
Application method:	Shake the jar well before use. Use a paint brush to apply thin layers over the damaged area. When applying several layers leave 5 minutes between each layer for the product to evaporate. After at least 10 minutes and no more than 60 minutes remove excess paint using Innotec Repair Finish , Polish Block , Blue Plastic Card and Multi Wipes . See also the directions for use of the Innotec Stone Chip Repair Systems .
Dust dry:	± 5-10 minutes (at 20°C)
Curing time:	± 24 hours (at 20°C)
Recommended layer thickness:	The same depth as the stone chip damage
Cleaning of materials used:	With Innotec Thinning Agent
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	3 years in original, unopened packaging





Storage conditions: Store cool and dry

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

