

# Repaplast Colour Finish BC Gloss Black

Art.: 02.3100.5005  
Aerosol can 500 ml

Repaplast Colour Finish Better Care is a modern, professional plastic paint which is available in the most common OEM colours. This means that the product is extremely well suited to restoring repaired or weathered plastic parts to their original state with a minimum of effort.



Base:	Nitrocellulose-based synthetic resin lacquer
Density:	830 kg/m <sup>3</sup>
Consistency:	Liquid (ready-to-use in aerosol)
Flash point:	< 0°C
Temperature resistance:	-30°C to +100°C
UV resistance:	Excellent
Water resistance:	Excellent
Solvent resistance:	Reasonable
Application conditions:	+15°C to +30°C (max. 80% relative humidity)
Type of surface:	Just about all modern plastics and metals
Surface preparation:	The surface must be clean, dry and free of dust and grease. Sand the surface, preferably with a sanding block. Clean metal surfaces with Innotec <a href="#">Multisol</a> or Innotec <a href="#">Seal and Bond Remover</a> . Provide untreated metal with a primer (Innotec <a href="#">Speed Primer</a> or Innotec <a href="#">Zinc Coat</a> ). Clean plastic surfaces with Innotec <a href="#">Repaplast Cleaner Antistatic</a> . If you do not want to spray the plastic part completely, we recommend you a pre-treatment with Innotec <a href="#">Repaplast Primer New Formula</a> .
Application method:	Shake spray can well before use. Spraying distance 25-30 cm. Apply in several thin layers. When applying several layers leave 10 minutes for the product to evaporate in between. After use, invert can and spray until clear to clean the nozzle.
Dust dry:	± 12-14 minutes (20°C / 50% relative humidity)
Curing time:	2 hours (20°C / 65% relative humidity)
Recommended layer thickness:	Thin coats
Cleaning of materials used:	With Innotec <a href="#">Multisol</a>
Cleaning of hands:	With Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry





Type of batchcode:	F
Other details:	OEM approved
EAN Code:	5400563009864

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

