

## Masking Tape

Art.: 05.1339.0500

Roll 12,5 m

Masking Tape is a high-quality cover tape strengthened with a PET film and specially developed to protect rubber and parts of vehicles or objects that need to be covered.



Base:	PE coated paper with an acrylic glue layer
Dimensions:	12,5 m x 45 mm x 90 μ PET film 10 mm
Tensile strength:	35 N/cm
Elongation at break (%):	4,5%
Temperature resistance:	-20°C to +110°C
UV resistance:	Good
Water resistance:	Good
Solvent resistance:	Good
Type of surface:	Most surfaces
Surface preparation:	The surface must be clean, dry and free of grease.
Application method:	Remove the protective foil, push the PET film under the rubber and press down with enough tension in the opposite direction.
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry, at a temperature between +5°C and 20°C
Type of batchcode:	F
EAN Code:	5400563026106

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

