

## **TECHNICAL INFO**

## **Repaplast Primer New Formula**

Art.: 02.0135.9999 Aerosol can 500 ml

Repaplast Primer New Formula is a professional adhesion enhancer suitable for use on most types of plastics. Thanks to its unique improved formula, this product considerably enhances adhesive properties upon repairing, gluing and spraying.



Base:	Polymer based adhesion primer
Density:	700 kg/m³
Consistency:	Liquid (ready-to-use in aerosol)
Solvents:	Mixture of aromatic and aliphatic solvents
Flash point:	< 0°C
Temperature resistance:	-20°C to +80°C
Application conditions:	+10°C to +30°C (max. 80% relative humidity)
Type of surface:	The most common plastics, including polypropylene, polyethylene, polyurethane, elastomer mixes, ABS, TPO, etc. and difficult materials such as metal, stainless steel, (natural) stone, etc.
Surface preparation:	The surface must be clean, dry and free of grease. Sand down or roughen the surface depending on the subsequent treatment. Clean with Innotec Repaplast Cleaner Antistatic.
Application method:	Shake can well before use. Spraying distance ± 25 cm. Apply in one thin, even layer and allow to evaporate for at least 10 minutes. After use, invert can and spray until clear to clean the nozzle.
Open time:	24 hours
Drying time:	± 10 minutes (at 20°C)
Recommended layer thickness:	A thin, even layer
Paintability:	Excellent after curing
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	12 months in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
EAN Code:	5400563006726





This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.



A member of group PCS Innotec International N.V.