

## Dry Lube

Art.: 03.0123.6100

Aerosol can 500 ml

Dry Lube is a fast drying and silicone free lubricant that leaves a high-quality lubricating and sliding film on the treated surface. Thanks to its unique composition, this product provides a dry and almost invisible antistatic layer, thus reducing stick & slip resistance to zero.



Base:	Fluoropolymer
Density:	604 kg/m <sup>3</sup>
Consistency:	Liquid (ready-to-use in aerosol)
Solvents:	Aliphatic hydrocarbons
Flash point:	< 0°C
Temperature resistance:	-60°C to +280°C
Water resistance:	Good
Solvent resistance:	Not resistant to solvents
Acid resistance:	Very good. Also thoroughly tested against hydroxides such as nitric acid, hydrochloric acid, 30% potassium hydroxide, 30% sodium hydroxide.
Tests:	Registered by NSF (class H2), register number: 144035
Application conditions:	-15°C to +40°C
Type of surface:	Dry Lube can be applied to the most frequent surfaces such as ferrous and non-ferrous metals, wood, plastics, textiles, etc. This multi-purpose product is perfectly suitable for conveyer belts, dashboards, slides, machine parts etc. where the attraction of dust and dirt is to be avoided.
Surface preparation:	The surface must be clean, dry and free of dust and grease. Clean the surfaces with Innotec <a href="#">Multisol</a> .
Application method:	Shake can well during 2 minutes before use. Spray the product directly on the surface to be treated (spraying distance 15-20 cm). For best results, apply several thin layers.
Dust dry:	After ± 5 to 10 minutes (at 20°C)
Cleaning of materials used:	With Innotec <a href="#">Multisol</a> or Innotec <a href="#">Power Clean</a>
Cleaning of hands:	With Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	12 months in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F





EAN Code: 5400563015551

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

