

## **TECHNICAL INFO**

## Base Glue

Art.: 01.2100.9999 Tube 10 g

Base Glue is part of the Innotec Velours Repair System and the Innotec Velours Repair System - VW (VAS 6221). It is a flexible contact glue for gluing backing material to fabric or foam.



_	
Base:	Polyurethane resin
Density:	± 870 kg/m³
Consistency:	Thick fluid
Viscosity:	± 4500 mPa.s (at 25°C)
Solvents:	Mischung organischer Lösungsmittel
Temperature resistance:	-35°C to +95°C
Moisture resistance:	Good. Not resistant to prolonged contact with water.
Solvent resistance:	Moderate
Application conditions:	+15°C to +30°C
Type of surface:	Almost all modern upholstery
Surface preparation:	The surface must be clean, dry and free of grease.
Surface preparation: Application method:	The surface must be clean, dry and free of grease. Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System.
	Apply the glue directly from the tube to the repair area. See also the directions for use of the
Application method:	Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System.
Application method: Open time:	Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System. ± 10 minutes
Application method: Open time: Drying time:	Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System.   ± 10 minutes   24 hours
Application method: Open time: Drying time: Cleaning of materials used:	Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System.   ± 10 minutes   24 hours   With Innotec Velours Repair Remover
Application method: Open time: Drying time: Cleaning of materials used: Cleaning of hands:	Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System.   ± 10 minutes   24 hours   With Innotec Velours Repair Remover   With Innotec Safe Hand Clean Plus and water
Application method: Open time: Drying time: Cleaning of materials used: Cleaning of hands: Shelf life:	Apply the glue directly from the tube to the repair area. See also the directions for use of the Innotec Velours Repair System.   ± 10 minutes   24 hours   With Innotec Velours Repair Remover   With Innotec Safe Hand Clean Plus and water   24 months in original, unopened packaging

This technical info sheet replaces all previous versions.



A member of group PCS Innotec International N.V.



All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

