

## Total Power Grease

Art.: 03.0110.9999  
Aerosol can 500 ml

Total Power Grease is an extremely high-quality grease, which, due to its excellent pressure and temperature resistance, is ideal as a universal lubricant. When being applied the product initially is liquid, so it can penetrate deeply between the parts. After the propellant has evaporated away it leaves a beautiful, solid and pressure-resistant grease behind.



Base:	Calcium complex soap with EP additives
Density:	644 kg/m <sup>3</sup>
Consistency:	Pasty
Viscosity:	1-2 (NLGI)
Flash point:	< 0°C
Pressure resistance:	Very good, due to the addition of EP additives. 4 ball welding load: ± 250kg (according to IP-239)
Temperature resistance:	-20°C to +160°C
Peak temperature resistance:	230°C
Drop point:	> 250°C
Water resistance:	Good, resistant to cold and hot water
Acid resistance:	Good, resistant to weak acids
Corrosion resistance:	Very good, especially for copper and steel
Mechanical stability:	Good
Penetration ability:	Very good
Percentage of greasing agent:	17,3%
Application conditions:	-20°C to +40°C
Type of surface:	All kind of metals
Surface preparation:	The surface must be clean, dry, free of grease and non-corroded. Clean surfaces with Innotec <a href="#">Multisol</a> , Innotec <a href="#">Ultra Clean</a> or Innotec <a href="#">Power Clean</a> .
Application method:	Shake well before use. Spray directly on the part to be lubricated and leave a short time to evaporate.
Cleaning of materials used:	With Innotec <a href="#">Multisol</a> or Innotec <a href="#">Power Clean</a>
Cleaning of hands:	With Innotec <a href="#">Safe Hand Clean Plus</a> and water





Shelf life: 2 years in original, unopened packaging

Storage conditions: Store cool and dry

Type of batchcode: F

EAN Code: 5400563014974

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

