

## Deblock Oil XS

Art.: 03.1107.9999

Aerosol can 500 ml

Deblock Oil XS is a mix of quick rust dissolvers and lubricants, which is far more effective than ordinary penetrating oils. Thanks to very specific ingredients, the product provides, under extreme shear stress, such as when loosening rusty bolts or nuts, high quality interfacial lubrication to prevent re-seizing during disassembly.



Base:	Mineral oil dissolved in a mixture of solvents and Molybdenum disulfide (MoS <sub>2</sub> )
Density:	820 kg/m <sup>3</sup>
Consistency:	Liquid (ready-to-use in aerosol)
Viscosity:	± 2-3 mPa.s (20°C)
Flash point:	< 0°C
Pressure resistance:	Extremely good, due to MoS <sub>2</sub> content. Not suited, however, under constantly extremely severe circumstances.
Temperature resistance:	-180°C to +400°C
Water resistance:	Good. Contains waterresistant additions.
Penetration ability:	Very good
Percentage of greasing agent:	± 14%
Application conditions:	-20°C to +40°C
Type of surface:	All kind of metals
Surface preparation:	The surface must be clean, dry and free of grease.
Application method:	Shake well before use. Spray directly on part for treatment. Let it penetrate for at least 2-3 minutes and turn the part loose. If necessary, repeat treatment.
Cleaning of materials used:	With Innotec <a href="#">Multisol</a> or Innotec <a href="#">Power Clean</a>
Cleaning of hands:	With Innotec <a href="#">Safe Hand Clean Plus</a> and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
EAN Code:	5400563035702

This technical info sheet replaces all previous versions.





All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

