

Alu Scratch Repair Activator

Art.: 01.0137.9999
Aerosol can 150 ml

Alu Scratch Repair Activator is part of the Innotec Alu Scratch Repair System and is only used for accelerating the curing of [Alu Scratch Repair](#).



Base:	Aliphatic hydrocarbon
Density:	700 kg/m ³
Consistency:	Thin liquid
Viscosity:	± 25 mPa.s
Solvents:	Mixture of aliphatics
Flash point:	< 0°C
Application conditions:	+5°C to +35°C
Type of surface:	Almost all aluminium and metal surfaces
Surface preparation:	The surface must be clean, dry and free of grease. Clean the repair area using Innotec Repaplast Cleaner Antistatic (allow to evaporate for 5 minutes).
Application method:	Wait 30 seconds, then spray a thin layer of Alu Scratch Repair Activator over the part repaired with Innotec Alu Scratch Repair . After this, hardening will take place within a few seconds.
Cleaning of materials used:	With Innotec Multisol
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	3 years in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
EAN Code:	5400563000250

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. Only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no





responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

