

TECHNICAL INFO

Multisol 1 l

Art.: 04.0151.9999

11

Multisol is a professional degreaser specially developed to safely degrease the most common surfaces before gluing, sealing or any other activity.



Base:	Mixture of alcohol, aromatic and aliphatic hydrocarbons
Density:	± 760 kg/m³
Consistency:	Liquid
Viscosity:	± 2 mPa.s
Solvents:	Mixture of alcohol, aromatic and aliphatic hydrocarbons
Flash point:	< 0°C
Evaporation residue:	None, the product will evaporate completely.
Application conditions:	+5°C to +40°C
Type of surface:	The most common surfaces. Test first when using on plastics.
Application method:	Apply Multisol on a clean, dry and soft cloth and treat the surface. Rub dry with a clean, dry and soft cloth. If you intend to proceed with other jobs such as gluing, etc., leave to evaporate for approximately 10 minutes.
Cleaning of hands:	With Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.







For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.



